

# Coatema - R&D Solutions

## → Verticoater 500 (VC 04)

<b>Arbeitsbreite:</b>	500 mm
<b>Walzenbreite:</b>	600 mm
<b>Geschwindigkeit:</b>	0,2 - 8 m/min
<b>Zugspannung:</b>	15 - 150 N
<b>Kanaltemperatur:</b>	max. 230 °C
<b>Anschlusswert:</b>	ca. 55 kW
<b>Abluft:</b>	2.500 m <sup>3</sup> /h
<b>Umluft:</b>	2.000 m <sup>3</sup> /h
<b>Abmessungen (LxBxH):</b>	5.400 x 2.300 x 3.800 mm

## → Verticoater 500 (VC 04)

<b>Working Width:</b>	500 mm
<b>Roller Width:</b>	600 mm
<b>Operating Speed:</b>	0,2 - 8 m/min
<b>Tensile Strength:</b>	15 - 150 N
<b>Dryer Temperature:</b>	max. 230 °C
<b>Electrical Connections:</b>	approx. 55 kW
<b>Exhaust Air:</b>	2.500 m <sup>3</sup> /h
<b>Air Circulation:</b>	2.000 m <sup>3</sup> /h
<b>Dimensions (LxWxH):</b>	5.400 x 2.300 x 3.800 mm

